

# PACIFIC ASIAN ENTERPRISES, INC.

P.O. BOX FA  
DANA POINT, CALIFORNIA 92629 U.S.A.  
(714) 496-4848                      TELEX 182-285

MASON 44116, 44117, 44118

## SPECIFICATIONS

L.O.A.	43' 10 $\frac{1}{2}$ "
L.O.A. (CCA Rule)	43' 7 $\frac{1}{4}$ "
L.W.L. (DWL)	31' 9"
Beam	12' 3 $\frac{1}{4}$ "
Draft	6' 5"
Displacement to DWL	27,400
Ballast	9,400
Sail area - cutter	899 sq. ft.
Sail area - ketch	916 sq. ft.
Fuel capacity	147 gallons
Water capacity	205 gallons

## CONSTRUCTION:

Hull - hand laid to Lloyds +100 Al specifications with 10 full length longitudinal stringers  
Deck - molded FRP sandwich with optional teak  
Cabin - molded FRP sandwich with molded nonskid pattern  
Exterior trim - teak  
Cockpit sole - teak grate  
FRP weatherhood for sliding companionway hatch

## DECK EQUIPMENT:

Six s/s closed rail chocks  
Four 10 $\frac{1}{2}$ " bow and stern cleats  
Two 6 $\frac{1}{2}$ " midship cleats  
Full length teak handrails on cabin top  
S/S bow and stern pulpits  
Staysail sheet tracks  
Double life lines  
Deckplate for emergency tiller  
Winches:  
Primary winches: Lewmar No. 48 STC  
Secondary winches: Lewmar No. 30 C  
Main sheet: Lewmar No. 30 C  
Staysail halyard: Lewmar No. 30  
Jib halyard: Lewmar No. 30  
Main halyard: Lewmar No. 30  
Double bow roller to accommodate 45lb. CQR anchor; S/S and bronze  
Three dead lights

Stainless steel mast pulpits  
Stainless steel cowl vent protector  
Stainless steel pedestal pulpits

## SPARS & RIGGING:

Forespar aluminum mast and boom assembly with polyurethane paint  
Spreader lights, foredeck lights  
Nav-Tec stainless steel turnbuckles  
Complete running rigging  
Standing rigging: U.S. manufactured using Nav-Tec turnbuckles and stainless steel cable  
Blocks - Schaefer 08 series/Lewmar  
Main sheet traveler with double roller bearing cap, & traveler control system  
Internal halyards  
Dual internal reef system with C/L  
Mounted reef winch and internal topping lift (No. 30)

## SAILS:

Sobstad/Watts - main is 9oz., with 2 sets reef points  
Staysail - 8oz.  
Jib - 8.2oz., includes a tell tale window

## STEERING:

Pedestal with 34" wheel  
Emergency tiller

## VENTILATION:

Five FRP Dorade ventilation boxes. Each vent box has a large stainless steel cowl  
One low profile water trap vent over the aft cabin  
Four teak opening hatches with acrylic tops  
One teak companionway hatch  
Two aluminum ventilation hatches  
Opening ports are stainless steel:  
Three 7" x 14"  
Six 6" x 12"